

INDUSTRIAL FIELD REPORT

SEWAGE WATER CLEANING - TANKS



1 SITUATION

CP Kelco is a global producer of hydrocolloids. At the facility in Denmark they needed the floor of 2 sewage water tanks on 450 m² each to be recoated.

The facility could not live with a long shutdown time because of a 50 % reduction of production in the factory.

2 SOLUTION

LINE-X[®] XS-350 was sprayed 3.18 mm (1/8 inch) thick onto primed concrete creating a monolithic, impervious protective lining with tenacious adhesion. The difference in thickness was less than 4 % calculated over all 900 m² thanks to our skilled applicators.

3 AFTER APPLICATION

Each tank was completed in one week and back in service 12 hours after application.

INDUSTRIAL CUSTOMER

CP Kelco A/S
www.cpkelco.com

LOCATION

CP Kelco A/S
Ved Banen 16
DK- 4623 Lille Skensved
Denmark

APPLICATOR

LINE-X Protective Coatings
Denmark A/S
(+45) 39 30 33 88 |
kasper@line-x.dk

FORMULATION

Concrete moisture cured sealer/primer. LINE-X XS350
100% solids polyurea
sprayed on lining

APPLICATION SYSTEM

GRACO FOAMCAT 200
with Fusion Gun

For more information on LINE-X Industrial Coatings Division, please contact:

6 Hutton Centre Drive, Suite 500, Santa Ana, California USA 92707 | (800) 831-3232 (Office) | www.line-xicd.com

